

PLASTOFUSED

PLASTOFUSED
804200



KAMATEC
Consulting - Innovation - Production

Product Description

PlastoFused is designed for meticulous repair in the Automotive Sector.

The functionality of this system is based on the heating of plastic parts by a perfect ratio of constant temperature control and air.

N.B. Pictures are for illustration purposes only - actual products may differ from images

Technical Parameters

Operating voltage:	230V / ~ 50Hz
Power:	320W / 1,49 A
Temperature (adjustable):	160 ... 480°C / 320 ... 896°F
Length of hose:	1m
Display:	LCD (2-doubled spaced)

ACCESSORIES

804112
PP-EPDM



804116
ABS



Y.E.S.
YOUR EQUIPMENT SUPPLIER

Y.E.S. - Your Equipment Supplier

Longlake Industrial, Warehouse Unit 157/2,
8 Ranworth Crescent, Erf 156, Longlake Ext 23,
Modderfontein, 1645

Tel: +27 (0) 10 590 9444 Fax: +27 (0) 11 786 5996/7/8

Email: sales@yesrsa.co.za

Website: www.yesrsa.co.za

Reg. No. 97/10686/07

Contact the Y.E.S. Sales office on +27 (0) 010 590 9444 for more information.
Darrel: 083 926 7101 | Rocco: 060 519 7735 | Raj: 065 829 1217 | Mace: 082 442 4202



CAR-O-LINER

AVKOM COMPRESSOR



Fillon
Technologies

NITROHEAT