

RIVETING TOOL XPRESS 800 | STANDARD SET



Pictures are for illustration purposes only - actual products may differ from images

The modular technology of the device allows the adaptation of many function tools for different applications. The device system can be optionally combined with a series of hydraulic cylinders and designated C-brackets. The device system is supplemented by a multitude of special tools for customized applications.

PRODUCT SPECIFICATIONS

Vibration:	< 2.5 m/s ²
Air quality (ISO):	ISO 8573-1
Working pressure:	6 bar / 87 psi
Noise level:	75 dB(A)
Viscosity (OIL):	22-36mm ² /s (40° C)
PB Max:	800 bar
Filling Volume:	100 cm ³
Net Weight:	33.00kg
Gross Weight:	33.00kg
Working Temperature:	5-50° C/41-122° F

ITEMS SUPPLIED

- 1X Xpress 800 Basic unit
- 1X Xpress 800 cylinder SC35/25
- 1X Xpress 800 C-arm GC 80/40
- 1X Xpress 800 C-clamp GC 80/120
- 1X Xpress 800 C-clamp GC 140/240
- 1X Xpress 800 Tool Box RS-03
- 1X Xpress 800 Case
- 1X Xpress 800 Manual

Y.E.S. - Your Equipment Supplier

Longlake Industrial, Warehouse Unit 157/2, 8 Ranworth Crescent, Erf 156, Longlake Ext 23, Modderfontein, 1645

Tel: +27 (0) 10 590 9444 • Fax: +27 (0) 11 786 5996/7/8

Email: sales@yesrsa.co.za • Website: www.yesrsa.co.za • Reg. No: 97/10686/07



Mace Moodley
 National Operations Manager
 Cell No. 082 442 4202 Ext.702
 Email: macem@yesrsa.co.za

Raj Ramsammy
 Technical Sales Consultant
 Cell No. 065 829 1217 Ext.516
 Email: rajr@yesrsa.co.za

Darrel van der Kolff
 Sales and Technical Manager
 Cell No. 083 926 7101 Ext.703
 Email: darrelv@yesrsa.co.za

Rocco Boshoff
 Technical Sales Consultant
 Cell No. 060 519 7735 Ext.703
 Email: roccob@yesrsa.co.za