

Step 1

Attach the first shelf to the left and right side frames using the provided bolt and nuts. Only hand tight for now. (short bolts)

Sort bolts into different lengths: short, medium and long. The tapped screw points are for the handle - keep one side.

Step 2

Attach the second shelf to the left and right frames the provided bolt and nuts. Only hand tight for now. (short bolts)

Step 3

Slide to top shelf in at the top of the frame and make sure the holes align , then hand fasten them together with the bolts and nuts provided (short bolts)

Step 4

Attach the wheel support plate together with the smaller wheels. (there will be eight long bolts all the same size to go through all the plates)

Step 5

Slide the silver bar through the frame .Put the first washer on then the black large wheel , then the second washer , then lastly the lock caps. Repeat the process on the opposite side to complete the wheel assembly.

Step 6

Slip the aluminium between the left and right frame at the top , align the holes. Use the four tapped point screws to secure handle in place.

Step 7

Locate the plastic gun holder position on the side of the frame and fasten in place. (Note there are only two very long bolts to secure the holder in place)

Step 8

Attach the side rail to the opposite side of the frame. Then finally tighten all the bolts and nut securely.

Step 9

Place the dent puller on the top of the shelf and connect the three cables to the front. Make sure the small cable's groove lines up with the inlet's groove.

Step 10

Connect the rod with hammer to the front of the single side spot gun.

Step 11

Place your tool box on the second shelf where it is easily accessible.



Scan the QR code for a video demonstration of the assembly.

Contact your sales representative should you require further assistance with our products.

Address:

4 Andries Street South, Wynberg, JHB, 2090

Tel:

+27 (0) 10 590 9444

Email:

sales@yesrsa.co.za

Website:

www.yesrsa.co.za